Archive of SID.ir

Review Article

Emerging Technologies for Eco-Friendly Production of Bioethanol from Lignocellulosic Waste Materials

Francis-Dominic Makong Ekpan[1] | Merit Oluchi Ori[2] | Humphrey Sam Samuel[3*] | Odii Peter Egwuatu[4]

[1]*Department of BioTechnology Federal University of Technology Owerri, Nigeria*
[2]*Department of Microbiology Federal University of Technology Owerri, Nigeria*
[3]*Department of Chemical Sciences, Federal University Wukari, Taraba State, Nigeria*
[4]*Department of Anatomy, Ebonyi State University, Abakaliki, Nigeria*

Use yor device to scan and read the article online

Citation F. M. Ekpan, M. O. Ori, H. S. Samuel, O. P. Egwuatu. **Emerging Technologies for Eco-Friendly Production of Bioethanol from Lignocellulosic Waste Materials.** *Eurasian J. Sci. Technol.,* **2024**, *4*(3), 179-194.

https://doi.org/10.48309/EJST.2024.429106.1119

CC BY

Article info:
Received: 2023-12-06
Accepted: 2024-01-05
Available Online: 2024-01-27
ID: EJST-2312-1119
Checked for Plagiarism: Yes
Checked Language: Yes

Keywords:
Bioethanol, Lignocellulosic waste, Sustainable energy, Renewable energy, Agricultural residues, Forest biomass.

ABSTRACT

In the face of growing environmental concerns and the need for sustainable energy sources, the production of bioethanol from lignocellulosic waste materials has emerged as a promising solution. This study provides an overview of efforts to enhance the eco-friendly production of bioethanol from lignocellulosic waste, addressing both the environmental and economic aspects of this renewable energy source. Lignocellulosic waste materials, such as agricultural residues and forest biomass, offer a rich source of raw materials for bioethanol production. Their utilization not only reduces waste accumulation, but also decreases the dependency on finite fossil fuels. However, the challenge lies in the efficient conversion of these materials into bioethanol while minimizing environmental impacts. To achieve this, researchers have been exploring various strategies, including advanced pretreatment techniques, enzymatic hydrolysis, and microbial fermentation. These methods aim to increase bioethanol yields, reduce production costs, and minimize waste generation, thus promoting a more sustainable and eco-friendly approach. In addition, the integration of waste-to-bioethanol processes with existing industries and the development of circular bio-economies hold promise for economic viability. As the world shifts towards a more sustainable energy future, these advancements in bioethanol production from lignocellulosic waste materials play a crucial role in reducing greenhouse gas emissions and mitigating environmental impacts.

***Corresponding Author:Francis-dominic Makong Ekpan:** ekpanfrankdominic3@gmail.com*

Archive of SID.ir

Archive of SID.ir

Introduction

In an era marked by pressing environmental concerns and a growing demand for sustainable energy sources, the quest to enhance the eco-friendly production of bioethanol from lignocellulosic waste materials has garnered significant attention. Bioethanol, a renewable and low-carbon alternative to conventional fossil fuels, offers the potential to mitigate the adverse impacts of climate change while providing a cleaner source of energy. Lignocellulosic waste materials, comprising agricultural residues, forestry byproducts, and various organic wastes, have emerged as a valuable feedstock for bioethanol production [1]. The allure of lignocellulosic waste lies not only in its abundance but also in its potential to convert waste into a valuable resource. This transition embodies the essence of the circular economy, where waste materials find renewed purpose in the production of bioethanol, thus reducing the burden on landfills and diminishing the reliance on finite fossil resources [2]. However, unlocking the full potential of lignocellulosic waste for bioethanol production is not without its challenges. The efficient conversion of complex lignocellulosic structures into bioethanol demands innovative and sustainable approaches. This introduction sets the stage for a comprehensive exploration of the strategies, techniques, and technologies employed to overcome these challenges, focusing on the dual objectives of enhancing bioethanol yields and minimizing environmental impacts [3]. As the world seeks to transition towards a more sustainable and carbon-neutral future, the eco-friendly production of bioethanol from lignocellulosic waste materials stands as a beacon of hope, that exemplifies the intersection of environmental responsibility and renewable energy innovation. This discussion delves into the various facets of this pivotal endeavor, shedding light on the promising advances and the compelling opportunities it presents [4]. The aim of the study was to explore the eco-friendly production of bioethanol from lignocellulosic waste materials, emphasizing sustainability and waste management. It addresses the growing energy demand and the potential of this sustainable energy source. The study delves into bioethanol production from lignocellulosic waste materials, assessing its sustainability and impact on greenhouse gas emissions, and identifying challenges for future research to enhance efficiency and sustainability. The hypothesis suggests that the biofuel sector can become more sustainable and efficient using advanced technologies to produce bioethanol from lignocellulosic waste materials. The proposed procedures will maximize environmental impact while increasing bioethanol output. Our study aims to expand on the current understanding of sustainable biofuel production by integrating the most recent technological advancements for a more environmentally and financially feasible approach, although many studies have investigated bioethanol production from lignocellulosic materials. From the article we discussed, Lignocellulosic bioethanol production, sustainability assessment, waste as feedstock, technological advances, policy and regulation, and future perspectives .

Lignocellulosic Bioethanol Production

Lignocellulosic bioethanol production represents a pivotal juncture in the global transition towards sustainable and renewable energy sources. In the face of climate change and diminishing fossil fuel reserves, the utilization of lignocellulosic biomass as a feedstock for bioethanol production holds immense promise [5]. Lignocellulosic materials, such as agricultural residues, forestry waste, and dedicated energy crops, abound and provide an eco-friendly alternative for bioethanol production.

Lignocellulosic Biomass

Lignocellulosic biomass is a versatile source of organic material, primarily composed of three major components:cellulose, hemicellulose, and lignin. Cellulose, a linear polymer of glucose

Archive of SID.ir

Archive of SID.ir

molecules linked by beta-1,4-glycosidic bonds, is the most abundant and structurally stable component of lignocellulosic biomass. It provides the necessary sugar units for fermentation into ethanol and is found in various plant materials like corn stover, wood, and grasses. Hemicellulose, a branched polymer composed of various sugar monomers, has a less crystalline structure and is more easily hydrolyzed. Different types of lignocellulosic biomass contain varying proportions of hemicellulose, which can impact the efficiency of the conversion process. Lignin, a complex, irregular polymer, provides structural rigidity and protection to plant cells and is composed of phenolic compounds. It can be a barrier to efficient bioethanol production [6]. The types of lignocellulosic biomass can be broadly categorized into several groups:agricultural residues, forest residues, energy crops, municipal solid waste (MSW), and aquatic plants as shown in Figure 1. These variations in composition and types of lignocellulosic biomass provide flexibility and opportunities to tailor bioethanol production to local resources and environmental goals. Hardwoods often contain a higher proportion of lignin than softwoods.

Pretreatment

Pretreatment is a crucial step in bioethanol production, preparing lignocellulosic materials for efficient enzymatic hydrolysis and fermentation. Common pretreatment methods include physical pretreatment, chemical pretreatment, biological pretreatment, combined pretreatment, ionic liquid pretreatment, and dilute ammonia pretreatment. Physical pretreatment involves grounding or chipping biomass to increase surface area for enzymatic action, while chemical pretreatment involves dilute acid treatment to hydrolyze hemicellulose and break down lignin. Alkali solutions, such as sodium hydroxide or ammonia, are used to break down lignin and remove acetyl groups from hemicellulose, enhancing enzymatic digestibility. Organic solvents are used to remove lignin and hemicellulose, leaving behind cellulose-rich material. Biological pretreatment employs certain fungi and bacteria to break down lignocellulosic



Figure 1 Various types and sources of Lignocellulosic biomass [7]

Archive of SID.ir

Archive of SID.ir

materials, making them more amenable to enzymatic hydrolysis [8]. Combined pretreatment combines two or more approaches for better results, such as steam explosion followed by enzymatic treatment. Ionic liquid pretreatment dissolves lignin and disrupts the lignocellulosic structure, providing an effective pretreatment option. Dilute ammonia pretreatment, on the other hand, involves the treatment of biomass with dilute ammonia under mild conditions, helping to remove lignin and hemicellulose and being more environmentally friendly. The choice of pretreatment method depends on factors such as biomass type, desired end product, economic feasibility, and environmental considerations. The ultimate goal of pretreatment is to enhance the overall efficiency of bioethanol production by facilitating the release of fermentable sugars from the biomass while minimizing the formation of inhibitors that can affect fermentation [9].

Enzymatic Hydrolysis

Enzymatic hydrolysis is a crucial step in the production of bioethanol from lignocellulosic biomass. It involves the use of enzymes to break down complex carbohydrates, such as cellulose and hemicellulose, into simpler sugars that can be fermented into ethanol. The process begins with pretreatment, which removes or modifies lignin and hemicellulose, making the cellulose more accessible for enzymatic degradation. Enzymes, primarily cellulases and hemicellulases, are added to the pretreated biomass, breaking down cellulose and targeting hemicellulose [10]. Enzymatic hydrolysis occurs in a controlled environment with optimal pH and temperature conditions, cleaving the bonds between sugar molecules, releasing simple sugars like glucose, xylose, and mannose. The enzymatic action continues until a significant portion of the cellulose and hemicellulose has been converted into sugars, resulting in a hydrolysate. Enzyme recycling strategies are employed to reduce the cost of enzymes, with enzymes often recovered, purified, and reused in subsequent batches. The hydrolysate is then subjected to fermentation, where microorganisms typically yeast or bacteria metabolize the sugars and convert them into ethanol [11]. Distillation and purification are then performed to separate the ethanol from water and obtain high-purity ethanol for use as a biofuel or other applications. Enzymatic hydrolysis is a key process in lignocellulosic bioethanol production, but ongoing challenges include optimizing enzyme efficiency, reducing enzyme costs, and managing potential inhibitors. Advances in enzyme technology and process engineering continue to improve the overall yield and sustainability of bioethanol production from lignocellulosic materials [12].

Fermentation

Fermentation is a crucial step in the production of bioethanol from sugars derived from lignocellulosic biomass or other feedstocks. It involves the use of microorganisms, typically yeast or bacteria, to convert the sugars into ethanol and carbon dioxide. The process begins with the preparation of hydrolysate, which is a mixture of sugars derived from cellulose and hemicellulose. The choice of microorganism depends on the type of sugar present in the hydrolysate. Saccharomyces cerevisiae is commonly used for glucose fermentation, while other microorganisms like engineered strains may be employed for xylose and other sugars [13]. The selected microorganism is added to the hydrolysate, and the fermentation reaction occurs, where the microorganisms metabolize the sugars through a series of biochemical reactions. The yield of ethanol depends on factors such as the sugar concentration in the hydrolysate and the efficiency of the microorganism used. Fermentation continues until most available sugars have been converted into ethanol, which can take several days. Post-fermentation processing involves the recovery and refinement of the fermented broth, which contains ethanol, to produce high-purity ethanol suitable for biofuel or industrial applications. Fermentation plays a central role in converting sugars from lignocellulosic

Archive of SID.ir

Archive of SID.ir

biomass into a valuable and sustainable fuel source. Advances in biotechnology and strain engineering are continually improving the fermentation process for bioethanol production [14].

Challenges

The bioethanol production from lignocellulosic biomass faces several challenges, including securing consistent and affordable biomass supply, improving pretreatment efficiency, enhancing enzyme efficiency, and optimizing mixed-sugar fermentations. Enzymatic hydrolysis is slow and costly, and overcoming inhibitory compounds produced during pretreatment is crucial. Product inhibition and achieving high ethanol concentrations are also challenges. Bioethanol production processes are water and energy-intensive, posing sustainability and cost challenges. Waste management is essential, as toxic compounds can be difficult to handle and dispose of in an environmentally responsible manner [15]. Transitioning from laboratory-scale processes to commercial-scale production presents challenges related to process optimization, cost reduction, and ensuring consistent product quality. Compliance with regulations and policies related to environmental sustainability, safety, and biofuel standards can be complex and vary by region. Economic viability, especially when competing with fossil fuel industries, remains a significant challenge for the bioethanol sector [16]. Market competition from other renewable energy sources, such as biodiesel, hydrogen, and electric vehicles, adds challenges in securing a share of the transportation fuel market. Addressing these challenges requires ongoing research, development, and innovation in bioethanol production technologies, as well as collaborations between researchers, industry, and policymakers to create a more sustainable and economically viable bioethanol sector [17].

Sustainability Assessment

In an era marked by increasing environmental concerns, the search for sustainable and renewable sources of energy has gained significant momentum. Bioethanol, a type of biofuel, has emerged as a promising alternative to traditional fossil fuels due to its potential to reduce greenhouse gas emissions and dependence on non-renewable resources [18]. Lignocellulosic bioethanol, produced from waste biomass, presents a particularly appealing opportunity for sustainable energy production [19].

Environmental Sustainability

Lignocellulosic biomass production has a lower carbon footprint than other forms of biomass or fossil fuels, but its environmental impact can vary depending on factors such as feedstock type, cultivation practices, harvesting methods, and processing technologies [20]. It is often considered more environmentally friendly compared to other forms of biomass or fossil fuels. However, it is important to assess the specific environmental impacts in different contexts. Greenhouse gas emissions are typically offset by the CO_2 absorbed during biomass growth, making it a carbon-neutral process [21]. Land-use changes and transportation emissions can increase emissions. Land use and biodiversity are critical considerations, as converting natural habitats into biomass plantations can disrupt local ecosystems and reduce biodiversity [22]. Sustainable biomass production should focus on using marginal or degraded lands to minimize these impacts. Water usage is another important factor in environmental impact assessment, as some biomass crops may require significant water resources, leading to water scarcity issues [23]. Sustainable biomass production methods aim to minimize or eliminate the use of pesticides and fertilizers through integrated pest management and nutrient recycling. Soil health can be affected by biomass production, particularly if intensive cultivation practices are employed. Implementing practices like crop rotation and no-till farming can help maintain soil health. Optimizing transportation logistics and using renewable energy sources in processing

Archive of SID.ir

Archive of SID.ir

facilities can reduce environmental impacts. Advanced biomass conversion technologies can help minimize emissions. Responsible waste and residue management is essential to avoid environmental pollution. Biosecurity measures are essential to prevent the introduction of invasive species or diseases associated with certain biomass crops.

Economic Sustainability

The economic viability and cost-effectiveness of lignocellulosic biomass production and conversion into biofuels, particularly bioethanol, are crucial factors in determining its feasibility as a sustainable energy source [24]. Factors such as feedstock costs, conversion technology, operational costs, economies of scale, market prices, government incentives and policies, research and development, financial risks, environmental regulations, and co-products can significantly impact the economic viability of this process [25]. Feedstock costs are influenced by factors such as the type of used feedstock, its availability, and proximity to the processing facility. Advanced technologies like biochemical processes and thermochemical processes may require higher upfront capital investments but offer higher efficiency and product yields. Operational costs include labor, energy, maintenance, and process optimization [26]. Economies of scale can lower production costs for large-scale production facilities; while smaller facilities may have higher per-unit production costs due to less efficient resource utilization. Market prices for bioethanol can vary based on regional demand, government policies, and competition with other fuels. Government incentives, subsidies, and tax credits can make lignocellulosic bioethanol production economically viable, making it more competitive with fossil fuels. Investment in research and development can improve the efficiency of bioethanol production processes and reduce costs [27]. Financial risks, stringent environmental regulations, and the utilization of co-products generated during the bioethanol production process can also enhance cost-effectiveness.

Social Sustainability

Lignocellulosic bioethanol production from wastes has significant social impacts, including job creation, community involvement, and social responsibility. The industry can create jobs at various stages of the value chain, such as feedstock collection, processing, logistics, and plant operation, thereby positively impacting local and regional economies. It also stimulates indirect employment opportunities, including retail and services sectors and the production and supply of goods and services required by the bioethanol industry. Community involvement is crucial, as it involves local communities in feedstock sourcing, outreach, and collaboration. Partnerships with farmers, forest owners, and waste management companies can create economic opportunities [28]. Bioethanol production facilities can educate communities about the industry's environmental and economic benefits, building positive relationships and addressing concerns. Social responsibility involves ensuring safety and health standards for employees and residents, respecting indigenous rights, and engaging in consultation and consent processes. Economic development can be achieved by diversifying local economies, reducing dependence on a single industry, and generating tax revenue for local infrastructure [29]. Investing in workforce development and stakeholder engagement fosters trust and accountability in the industry, ensuring long-term employment opportunities and maintaining positive relationships.

Waste as Feedstock

Types of Waste

Lignocellulosic bioethanol production has gained prominence for its utilization of various waste materials as feedstock. These waste materials are typically categorized into several types:

a. *Agricultural Residues*:Agricultural waste materials are abundant and serve as

Archive of SID.ir

Archive of SID.ir

valuable feedstock for bioethanol production. Crop residues like corn Stover, wheat straw, sugarcane bagasse, and rice husks contain significant lignocellulosic content [30].

b. *Forestry Residues*:Waste from the forestry industry, such as wood chips, sawdust, and tree bark, are excellent sources of lignocellulose, making them suitable for bioethanol production [31].

c. *Municipal Solid Waste (MSW)*:Components of municipal solid waste, including paper waste, yard waste, and food waste, offer diverse feedstock options for bioethanol production [32].

d. *Industrial Waste*:Various industrial processes generate waste materials that can be repurposed for bioethanol production. Examples include paper mill waste and distillery waste [33].

e. *Algal Biomass*:Algal biomass derived from wastewater treatment processes and microalgae cultivation are emerging as sustainable waste-derived feedstock options.

Benefits and Challenges

i. Advantages of Utilizing Waste as Feedstock

a. *Abundance and Low Cost*:Waste materials are often readily available and are considered low-cost or even free, which substantially reduces the feedstock expenses [34].

b. *Waste Diversion*:Incorporating waste materials into bioethanol production serves the dual purpose of waste diversion from landfills, significantly reducing environmental burdens [34].

c. *Circular Economy*:The utilization of waste as bioethanol feedstock aligns with the principles of a circular economy by converting waste into a valuable resource, thereby contributing to sustainable waste management and resource conservation.

ii. Challenges of Utilizing Waste as Feedstock

a. *Feedstock Variability*:One of the major challenges is the variability in the composition of waste feedstock. Different waste sources can have significantly different characteristics, which may require adjustments in processing methods [35].

b. *Pre-processing and Pretreatment*:Many waste materials necessitate pre-processing and pretreatment to remove impurities, reduce recalcitrance, and enhance the efficiency of lignocellulose conversion. Pretreatment methods can include steam explosion, organosolv, ionic liquids, and acid/enzymatic treatments [36].

c. *Regulatory and Environmental Considerations*:Utilizing waste as feedstock requires careful consideration of regulatory and environmental factors, particularly in the case of municipal solid waste. Addressing potential contaminants and pollutants is essential to ensure the quality and safety of the bioethanol product [37].

Technological Advances

Innovative Technologies

Recent advancements in lignocellulosic bioethanol production have ushered in transformative changes to enhance efficiency and sustainability. These include:

a. *Pretreatment Technologies*:Innovations in pretreatment methods have been instrumental in making lignocellulosic feedstock more amenable to enzymatic

Archive of SID.ir

Archive of SID.ir

hydrolysis. These methods include steam explosion, organosolv, ionic liquids, and acid/enzymatic pretreatments [38].

b. *Enzymatic Hydrolysis*:Improved enzyme cocktails, tailored for specific feedstocks and conditions, have revolutionized the breakdown of lignocellulose. Engineered microorganisms are being developed for enhanced enzyme production and efficiency.

c. Fermentation:Ethanol-tolerant microorganisms have been developed, enabling more efficient and higher-yield fermentation of sugars to ethanol. Consolidated bioprocessing (CBP) strategies, employing a single microorganism for both hydrolysis and fermentation, are also being explored for cost-effective bioethanol production [39].

d. *Biorefinery Concept*:The integration of bioethanol production with the generation of other valuable products, such as bioplastics and biofuels, represents a significant breakthrough. Biorefineries aim to maximize resource utilization and minimize waste in the bioethanol production process [40].

Biotechnology and Genetic Engineering

Genetic modifications have played a pivotal role in improving biomass conversion and the efficiency of lignocellulosic bioethanol production:

a. *Microbial Strain Engineering*:Genetic engineering has led to the development of robust and efficient yeast and bacterial strains for ethanol production. Metabolic engineering strategies have been employed to enhance sugar utilization and increase ethanol yield. These advancements have helped overcome challenges related to the toxicity of ethanol on microorganisms [41].

b. *Enzyme Engineering*:Advances in enzyme engineering have yielded highly efficient enzymes for the breakdown of lignocellulose. This includes enhancing the activity, thermal stability, and resistance to inhibitors of enzymes used in the hydrolysis process [42].

c. *Biotechnology for Pretreatment*:Designer microbes have been created for lignin degradation and removal. This reduces the need for harsh chemical pretreatments and offers a more environmentally friendly and cost-effective approach [43].

Policy and Regulation

Ensuring the sustainability of lignocellulosic bioethanol production from waste requires policy and regulation. In order to phase out subsidies for fossil fuels with low efficiency and to uphold the temperature target set forth in the Paris Agreement, the UK parliament approved legislation and measures. Policy and sustainability factors were taken into consideration in an evaluation of the sustainability of lignocellulosic bioethanol production from wastes in Iceland. Efficient and effective pretreatment of biomass is essential for the sustainability and economic feasibility of the bioethanol production process from lignocellulosic biomass [44]. Conventional pretreatment techniques including organic solvents, mineral acids, and alkalis generate inhibitory chemicals that harm the environment and obstruct the enzymatic saccharification process, as well as discharge hazardous effluents. By introducing the idea of forest biorefinery, the use of sawdust from the sawmill sector for the manufacture of biofuel encourages the local valorization of wood waste. For the production of lignocellulosic bioethanol from waste to be sustainable, policy and regulation are crucial. Furthermore,

Archive of SID.ir

Archive of SID.ir

essential to the process's sustainability and financial viability is the efficient and effective preprocessing of biomass. A promising, economical raw resource that encourages the localization of wood waste value is sawdust from the sawmill sector used in the production of biofuel [45].

Government Incentives

The promotion of the sustainability of lignocellulosic bioethanol production from waste is mostly dependent on government incentives. These financial incentives are frequently intended to lower greenhouse gas emissions and encourage the development and usage of renewable energy sources. The following typical laws and financial incentives can support the production of lignocellulosic bioethanol in a sustainable manner:

i. *Renewable Fuel Standards (RFS)*:Laws enacted by governments' mandate that a specific proportion of fuels used in transportation originate from renewable resources, like lignocellulosic bioethanol. Producers of bioethanol may find a guaranteed market if RFS compliance is achieved.

ii. *Tax Credits and Subsidies*:To lower the cost of production for bioethanol manufacturers, governments may offer tax credits, grants, or subsidies. This can take the form of direct subsidies for bioethanol producing plants or investment or production tax credits.

iii. *Loan Guarantees and Financing Programs*:By assisting bioethanol producers in obtaining funding for the building and operation of their facilities at lower interest rates, government-backed loan guarantees and financing programs can increase their economic viability.

iv. *Feedstock Assistance*:Supportive initiatives that help with the acquisition of feedstock, such as waste products and agricultural residues, can increase the sustainability and cost-effectiveness of lignocellulosic bioethanol production [46].

v. *Carbon Pricing and Emissions Trading*:By putting in place carbon pricing measures like carbon taxes or cap-and-trade programs, we might inadvertently encourage the use of sustainable bioethanol as a low-carbon substitute by providing financial incentives for cutting greenhouse gas emissions.

vi. *Research and Innovation Challenges*:Governments might set up challenges and competitions to encourage creative approaches to the production of lignocellulosic bioethanol. Research and development initiatives might be motivated by awards and recognition [47].

vii. *Export and Trade Support*:By granting bioethanol producers access to foreign markets, trade agreements and export incentives can help them increase their supplier base.

viii. *Education and outreach*:To educate the public, businesses, and investors on the advantages of sustainable bioethanol production, governments might fund public awareness campaigns and educational initiatives.

By making the lignocellulosic bioethanol business more competitive on the market and environmentally sustainable, these rules and incentives foster its expansion. Countries may have different policies in place, but the general objective is to hasten the shift to a low-carbon and more sustainable transportation fuel industry [48].

Challenges and Barriers

To assure sustainability, lignocellulosic bioethanol production from waste should overcome a number of regulatory obstacles. These are a few of the difficulties:

Archive of SID.ir

Archive of SID.ir

i. *Nature of biomass as recalcitrant*:The complicated structure of lignocellulosic biomass makes it difficult to ferment into sugars, which complicates the process of producing bioethanol.

ii. *Cost of production*:Compared to conventional fossil fuels, the cost of manufacturing bioethanol from lignocellulosic waste is still expensive, which reduces its marketability.

iii. *Production technology viability*:It is challenging to scale up the production process because bioethanol production from lignocellulosic waste requires sophisticated technologies that are still in the research and development stage [49].

iv. *Waste management rules*:Inadequate waste management legislation may make it more difficult to collect and use lignocellulosic waste as a feedstock for the manufacture of bioethanol.

Governments can encourage the use of lignocellulosic waste as feedstock for bioethanol production by offering incentives like tax credits, subsidies, and money for research and development. This will help to overcome these regulatory obstacles. These difficulties can also be addressed by the development of economical and efficient methods for producing bioethanol from lignocellulosic waste [50].

Case studies

One effective example of sustainable lignocellulosic bioethanol production is Project Liberty, a joint venture between POET and DSM. This institution opened its doors for business in 2014 and is situated in Emmetsburg, Iowa. Its main source of feedstock is maize stover, a waste product left in the field after corn is harvested. The project presents a new method of producing bioethanol and other products from lignocellulosic biomass. It contributes significantly to the reduction of greenhouse gas emissions and has an annual production capacity of 25 million gallons of cellulosic ethanol. The feasibility of turning agricultural waste into bioethanol on a large scale for commercial use has been proven by Project Liberty [51]. Likewise, Abengoa is a successful bioethanol production facility and a worldwide renewable energy enterprise. Both in Spain and the US, they have participated in lignocellulosic bioethanol initiatives. The company makes cellulosic ethanol at its Salamanca plant in Spain by processing wheat straw and other agricultural leftovers. Abengoa's Hugoton plant in Kansas, USA, produces bioethanol from various lignocellulosic feedstocks, such as maize stover and wheat straw. The production of low-carbon biofuels, sustainable agriculture, and waste reduction have all benefited from these initiatives. POET-DSM Project Alpha (United States):Another noteworthy example is POET-DSM's Project Alpha, situated in Project LIBERTY, South Dakota. The goal of this study was to increase the production of cellulosic bioethanol from feedstock, such as maize cobs, leaves, husks, and stalks. A thorough evaluation of the sustainability of lignocellulosic bioethanol production from different waste sources was carried out in Iceland. According to the study, using trash as a feedstock for the manufacture of bioethanol can lower greenhouse gas emissions and support sustainable waste management techniques. A second-generation biorefinery recycled industrial and agricultural lignocellulosic waste for the production of bioethanol using a circular bioeconomy concept. The strategy sought to create a closed-loop system to maximize resources with added value from trash, supporting sustainability in the process [52].

Some of the impacts of these initiatives are as follow:

i. *Decreased Greenhouse Gas Emissions*:When compared to the usage of conventional fossil fuels, these initiatives considerably cut greenhouse

Archive of SID.ir

Archive of SID.ir

gas emissions. Their utilization of waste materials and agricultural residues helps reduce the transportation fuels' carbon footprint.

ii. *Waste Utilization*:These projects' success shows that lignocellulosic bioethanol production may efficiently use waste products and agricultural wastes, lowering the environmental impact of waste disposal.

iii. *Energy Security*:These projects help to provide energy security by reducing reliance on fossil fuels, which is crucial for energy diversification, by manufacturing bioethanol from non-food feedstocks.

iv. *Rural Economic Development*:By fostering local agriculture and generating jobs, these initiatives frequently help rural areas. Through the sale of agricultural leftovers, they can boost economic growth and give farmers more money [53].

Future Perspectives

Future prospects for the environmentally friendly manufacture of lignocellulosic bioethanol from waste are bright, as current research and development efforts are focused on enhancing the process' sustainability and efficiency. To create a closed-loop system that maximizes the value-added materials extracted from waste, lignocellulosic waste from industry and agriculture can be recycled for the production of bioethanol using a circular bioeconomy approach. Research and development efforts are still on to enhance or create suitable technology that can effectively convert lignocellulosic waste into bioethanol at a low cost of production. This covers the creation of economical and successful pretreatment techniques as well as enzymatic hydrolysis and fermentation procedures. Furthermore, a cutting-edge method for converting lignocellulosic biomass to ethanol while producing zero waste has been presented. This method can lessen the negative environmental effects of producing bioethanol and encourage sustainability. Future research and development efforts to increase the process' sustainability and efficiency bode well for the generation of sustainable lignocellulosic bioethanol from waste. Technological developments, the circular bioeconomy, and zero-waste biorefineries are a few future outlooks that can support sustainable bioethanol production [54].

Research Gaps

Even with the advancements in sustainable lignocellulosic bioethanol production from waste, several research gaps still need to be filled. The following are some topics that require more study:

i. *Effective and economical pretreatment techniques*:A critical stage in the manufacture of bioethanol is the pretreatment of lignocellulosic biomass. To break down the complex structure of lignocellulosic biomass into fermentable sugars, effective and economical pretreatment procedures are required.

ii. *Enzymatic hydrolysis and fermentation processes*:These are also essential phases in the manufacture of bioethanol, and more effective and economical methods are required to convert lignocellulosic waste into bioethanol at the lowest possible cost of production. Regulations and policies for waste management are required in order to promote the collection and use of lignocellulosic waste as a feedstock for the manufacture of bioethanol [55].

iii. *Technological developments*:Research and development efforts are still on to enhance or create suitable technology that can effectively convert lignocellulosic waste into bioethanol at a low cost of production. To create more effective and affordable technology, additional research in this field is still required. To

Archive of SID.ir

Archive of SID.ir

support sustainable lignocellulosic bioethanol production from trash, further research is required to create effective and affordable pretreatment techniques, enzymatic hydrolysis and fermentation methods, and waste management regulations. Furthermore, more study is required to create more economical and efficient methods for producing bioethanol from lignocellulosic waste [56].

Conclusion

The quest for enhancing the eco-friendly production of bioethanol from lignocellulosic waste materials is not merely an endeavor to find an alternative fuel source; it is a commitment to addressing the complex challenges of sustainability, climate change mitigation, and waste management. As the world grapples with the urgent need to transition from finite fossil fuels to renewable energy sources, lignocellulosic biomass stands as a valuable resource, abundant and diverse, ready to play a pivotal role in the energy landscape of the future. In the course of this review, we have explored the multifaceted nature of this topic, beginning with the recognition of bioethanol as a renewable and eco-friendly fuel source. Its significance lies not only in its potential to reduce greenhouse gas emissions, but also in its capacity to transform waste materials into valuable energy resources, alleviating the burden on landfills and incineration. Sustainability in this context encompasses not only the environmental aspects, but also the economic viability of the production process. Through various pretreatment methods, enzymatic hydrolysis, and fermentation, lignocellulosic biomass can be transformed into ethanol, but the journey is not without its share of challenges. Our exploration of these challenges, including biomass availability, pretreatment efficiency, enzyme cost, microorganism tolerance, and many others, underscores the complexity of the bioethanol production process. These challenges are not insurmountable but necessitate innovative solutions, research advancements, and continuous improvement in technology. The study suggests further research on enzymatic pretreatment techniques, microbial strain optimization, innovative bioreactor design, green solvent integration, and life cycle assessment for eco-friendly bioethanol production from lignocellulosic waste materials, promoting sustainable energy solutions. The path forward is marked by the pursuit of green technologies, circular bioeconomies, and the development of more efficient and environmentally friendly processes. As we have observed, the bioethanol industry is evolving, seeking to optimize every step of the production process, reduce waste generation, and maximize yield. These efforts are not only commendable but are imperative for the industry's growth and long-term sustainability. Enhancing the eco-friendly production of bioethanol from lignocellulosic waste materials is not just a scientific or industrial endeavor; it is a commitment to a more sustainable and greener world. It is a recognition that our energy choices can align with our environmental responsibilities. While challenges persist, the relentless pursuit of solutions and the collaboration of researchers, industry leaders, and policymakers provide hope for a future where bioethanol becomes an integral component of our sustainable energy landscape. This journey towards an eco-friendly bioethanol production process from lignocellulosic waste is not only promising, but also essential in our pursuit of a cleaner, greener, and more sustainable energy future.

Conflict of Interest

The authors declare that there is no conflict of interest in this study.

Funding

Not applicable.

Informed Consent Statement

Not applicable.

Ethical approval statement

Not applicable.

Archive of SID.ir

Archive of SID.ir

ORCID

Francis-Dominic Makong Ekpan
https://www.orcid.org/0009-0009-4822-7005
Merit Oluchi Ori
https://www.orcid.org/0009-0005-9259-5842
Humphrey Sam Samuel
https://www.orcid.org/0009-0001-7480-4234
Odii Peter Egwuatu
https://www.orcid.org/0009-0004-0662-9077

References

[1] Bušić A., Marđetko N., Kundas S., Morzak G., Belskaya H., Ivančić Šantek M., Komes D., Novak S., Šantek B., Proizvodnja bioetanola iz obnovljivih sirovina te njegovo odvajanje i pročišćavanje:pregled, *Food Technology and Biotechnology*, 2018, **56**:289 [Crossref], [Google Scholar], [Publisher]

[2] Devi A., Bajar S., Kour H., Kothari R., Pant D., Singh A., Lignocellulosic biomass valorization for bioethanol production:a circular bioeconomy approach. *Bioenergy Research*, 2022, **15**:1820 [Google Scholar], [Publisher]

[3] Mohanty B., Abdullahi I.I., Bioethanol production from lignocellulosic waste-a review. *Biosciences Biotechnology Research Asia,* 2016, **13**:1153 [Crossref], [Google Scholar], [Publisher]

[4] Mujtaba M., Fracet L., Fazeli M., Mukherjee S., Savassa S.M., de Medeiros G.A., Santo Pereira A.D.E., Mancini S.D., Lipponen J., Vilaplana F., Lignocellulosic biomass from agricultural waste to the circular economy:A review with focus on biofuels, biocomposites and bioplastics, *Journal of Cleaner Production*, 2023, 136815. [Crossref], [Google Scholar], [Publisher]

[5] Broda M., Yelle D.J., Serwańska K., Bioethanol production from lignocellulosic biomass—challenges and solutions, *Molecules*, 2022, **27**:8717 [Crossref], [Google Scholar], [Publisher]

[6] Tran T.T.A., Le T.K.P., Mai T.P. , Nguyen D.Q., Bioethanol production from lignocellulosic biomass. *Alcohol Fuels-Current Technologies And Future Prospect*,2019, 1 [Crossref], [Google Scholar], [Publisher]

[7] Tripathi N., Hills C.D., Singh R.S., Atkinson C.J., Biomass waste utilisation in low-carbon products:harnessing a major potential resource, *NPJ Climate and Atmospheric Science*, 2019, **2**:35 [Crossref], [Google Scholar], [Publisher]

[8] Xu Z., Huang F., Pretreatment methods for bioethanol production, *Applied Biochemistry and Biotechnology*, 2014, **174**:43 [Crossref], [Google Scholar], [Publisher]

[9] Shukla A., Kumar D., Girdhar M., Kumar A., Goyal A., Malik T., Mohan A., Strategies of pretreatment of feedstocks for optimized bioethanol production:distinct and integrated approaches, *Biotechnology for Biofuels and Bioproducts*, 2023, **16**:44 [Crossref], [Google Scholar], [Publisher]

[10] Vasić K., Knez Ž., Leitgeb M., Bioethanol production by enzymatic hydrolysis from different lignocellulosic sources, *Molecules*, 2021, **26**:753 [Crossref], [Google Scholar], [Publisher]

[11] Volynets B., Ein-Mozaffari F., Dahman Y., Biomass processing into ethanol:pretreatment, enzymatic hydrolysis, fermentation, rheology, and mixing, *Green Processing and Synthesis*, 2017, **6**:1 [Crossref], [Google Scholar], [Publisher]

[12] Yuan Y., Jiang B., Chen H., Wu W., Wu S., Jin Y., Xiao H., Recent advances in understanding the effects of lignin structural characteristics on enzymatic hydrolysis, *Biotechnology for Biofuels*, 2021, **14**:1 [Crossref], [Google Scholar], [Publisher]

[13] Shukla A., Kumar D., Girdhar M., Kumar A., Goyal A., Malik T., Mohan A., Strategies of pretreatment of feedstocks for optimized bioethanol production:distinct and integrated approaches, *Biotechnology for Biofuels and Bioproducts*, 2023, **16**:44 [Crossref], [Google Scholar], [Publisher]

Archive of SID.ir

Archive of SID.ir

[14] Phwan C.K., Ong H.C., Chen W.H., Ling T.C., Ng E.P., Show P.L., Overview:comparison of pretreatment technologies and fermentation processes of bioethanol from microalgae, *Energy Conversion and Management*, 2018, **173**:81 [Crossref], [Google Scholar], [Publisher]

[15] Dimos K., Paschos T., Louloudi A., Kalogiannis K.G., Lappas A.A., Papayannakos N., Kekos D., Mamma D., Effect of various pretreatment methods on bioethanol production from cotton stalks, *Fermentation*, 2019, **5**:5 [Crossref], [Google Scholar], [Publisher]

[16] Bender L.E., Lopes S.T., Gomes K.S., Devos R.J.B., Colla L.M., Challenges in bioethanol production from food residues, *Bioresource Technology Reports*, 2022, 101171 [Crossref], [Google Scholar], [Publisher]

[17] Merritt H., Barragán-Ocaña A., The impact of market factors on the development of eco-friendly energy technologies:the case of bioethanol, *Clean Technologies and Environmental Policy*, 2021, 1 [Crossref], [Google Scholar], [Publisher]

[18] Jeswani H.K., Chilvers A., Azapagic A., Environmental sustainability of biofuels:a review, *Proceedings of the Royal Society A*, 2020, **476**:20200351. [Crossref], [Google Scholar], [Publisher]

[19] Safarian S., Unnthorsson R., An assessment of the sustainability of lignocellulosic bioethanol production from wastes in Iceland, *Energies*, 2018, **11**:1493 [Crossref], [Google Scholar], [Publisher]

[20] Liu W.J., Yu H.Q., Thermochemical conversion of lignocellulosic biomass into mass-producible fuels:emerging technology progress and environmental sustainability evaluation, *ACS Environmental Au*, 2021, **2**:98 [Crossref], [Google Scholar], [Publisher]

[21] Patel A.D., Zabeti M., Seshan K., Patel M.K., Economic and environmental assessment of catalytic and thermal pyrolysis routes for fuel production from lignocellulosic biomass, *Processes*, 2020, **8**:1612 [Crossref], [Google Scholar], [Publisher]

[22] Marques A., Martins I.S., Kastner T., Plutzar C., Theurl M.C., Eisenmenger N., Huijbregts M.A., Wood R., Stadler K., Bruckner M., Canelas J., Increasing impacts of land use on biodiversity and carbon sequestration driven by population and economic growth, *Nature Ecology & Evolution*, 2019, **3**:628 [Crossref], [Google Scholar], [Publisher]

[23] Stenzel F., Greve P., Lucht W., Tramberend S., Wada Y., Gerten D., Irrigation of biomass plantations may globally increase water stress more than climate change, *Nature Communications*, 2021, **12**:1512 [Crossref], [Google Scholar], [Publisher]

[24] Broda M., Yelle D.J., Serwańska K., Bioethanol production from lignocellulosic biomass—challenges and solutions, *Molecules*, 2022, **27**:8717 [Crossref], [Google Scholar], [Publisher]

[25] Blasi A., Verardi A., Lopresto C.G., Siciliano S., Sangiorgio P., Lignocellulosic agricultural waste valorization to obtain valuable products:An overview, *Recycling*, 2023, **8**:61 [Crossref], [Google Scholar], [Publisher]

[26] Bušić A., Marđetko N., Kundas S., Morzak G., Belskaya H., Ivančić Šantek M., Komes D., Novak S., Šantek B., Proizvodnja bioetanola iz obnovljivih sirovina te njegovo odvajanje i pročišćavanje:pregled, *Food Technology and Biotechnology*, 2018, **56**:289 [Crossref], [Google Scholar], [Publisher]

[27] Devi A., Bajar S., Kour H., Kothari R., Pant D., Singh A., Lignocellulosic biomass valorization for bioethanol production:a circular bioeconomy approach, *Bioenergy Research*, 2022, **15**:1820 [Crossref], [Google Scholar], [Publisher]

[28] Saini J.K., Saini R., Tewari L., Lignocellulosic agriculture wastes as biomass feedstocks for second-generation bioethanol production:concepts and recent developments,

Archive of SID.ir

Archive of SID.ir

2015, **3**:337 [Crossref], [Google Scholar], [Publisher]

[29] Ştefănescu-Mihăilă R.O., Rural economy and bioethanol production. *Sustainability*, 2016, **8**:1148 [Crossref], [Google Scholar], [Publisher]

[30] Zhu J.Y., Pan X., Zalesny R.S., Pretreatment of woody biomass for biofuel production:energy efficiency, technologies, and recalcitrance, *Applied Microbiology and Biotechnology*, 2010, **87**:847 [Google Scholar], [Publisher]

[31] Jin M., Gunawan C., Balan V., Dale B.E., Consolidated bioprocessing (CBP) of AFEX™-pretreated corn stover for ethanol production using Clostridium phytofermentans at a high solids loading, *Biotechnology and Bioengineering*, 2012, **109**:1929 [Crossref], [Google Scholar], [Publisher]

[32] Xiao B., Sun X., Sun R., Chemical, structural, and thermal characterizations of alkali-soluble lignins and hemicelluloses, and cellulose from maize stems, rye straw, and rice straw, *Polymer Degradation and Stability*, 2001, **74**:307 [Crossref], [Google Scholar], [Publisher]

[33] Ballesteros M., Oliva J.M., Manzanares P., Negro M.J., Ballesteros I., Ethanol production from paper material using a simultaneous saccharification and fermentation system in a fed-batch basis, *World Journal of Microbiology and Biotechnology*, 2002, **18**:559 [Crossref], [Google Scholar], [Publisher]

[34] Ekpan F.M., Ori M.O., Samuel H.S., Egwuatu O.P., The synergy of AI and Drug delivery: A Revolution in Healthcare, *International Journal of Advanced Biological and Biomedical Research*, 2024, **12**:45 [Crossref], [Publisher]

[35] Chundawat S.P., Beckham G.T., Himmel M.E., Dale B.E., Deconstruction of lignocellulosic biomass to fuels and chemicals, *Annual Review of Chemical and Biomolecular Engineering*, 2011, **2**:121 [Crossref], [Google Scholar], [Publisher]

[36] Taherzadeh M.J., Karimi K., Pretreatment of lignocellulosic wastes to improve ethanol and biogas production:a review, *International Journal of Molecular Sciences*, 2008, **9**:1621 [Crossref], [Google Scholar], [Publisher]

[37] Chen Y., Stevens M.A., Zhu Y., Holmes J., Xu H., Understanding of alkaline pretreatment parameters for corn stover enzymatic saccharification, *Biotechnology for Biofuels*, **2013**, **6**:1 [Crossref], [Google Scholar], [Publisher]

[38] Jin M., Gunawan C., Balan V., Dale B.E., Consolidated bioprocessing (CBP) of AFEX™-pretreated corn stover for ethanol production using Clostridium phytofermentans at a high solids loading, *Biotechnology and Bioengineering*, 2012, **109**:1929 [Crossref], [Google Scholar], [Publisher]

[39] Lynd L.R., Van Zyl W.H., McBride J.E., Laser M., Consolidated bioprocessing of cellulosic biomass:an update, *Current Opinion in Biotechnology*, 2005, **16**:577 [Crossref], [Google Scholar], [Publisher]

[40] Ragauskas A.J., Beckham G.T., Biddy M.J., Chandra R., Chen F., Davis M.F., Davison B.H., Dixon R.A., Gilna P., Keller M., Langan P., Lignin valorization:improving lignin processing in the biorefinery, *Science*, 2014, **344**:1246843 [Crossref], [Google Scholar], [Publisher]

[41] Turner T.L., Kim H., Kong I.I., Liu J.J., Zhang G.C., Jin Y.S., Engineering and evolution of Saccharomyces cerevisiae to produce biofuels and chemicals, *Synthetic Biology–Metabolic Engineering*, 2018, 175 [Crossref], [Google Scholar], [Publisher]

[42] Pereira J.H., Chen Z., McAndrew R.P., Sapra R., Chhabra S.R., Sale K.L., Simmons B.A., Adams P.D., Biochemical characterization and crystal structure of endoglucanase Cel5A from the hyperthermophilic Thermotoga maritima, *Journal of structural biology*, 2010, **172**:372 [Crossref], [Google Scholar], [Publisher]

[43] Bugg T.D., Ahmad M., Hardiman E.M., Rahmanpour R., Pathways for degradation of lignin in bacteria and fungi, *Natural Product Reports*, 2011, **28**:1883 [Crossref], [Google Scholar], [Publisher]

Archive of SID.ir

Archive of SID.ir

[44] Safarian S., Unnthorsson R., An assessment of the sustainability of lignocellulosic bioethanol production from wastes in Iceland, *Energies*, 2018, **11**:1493 [Crossref], [Google Scholar], [Publisher]

[45] Shahzadi T., Mehmood S., Irshad M., Anwar Z., Afroz A., Zeeshan N., Rashid U., Sughra K., Advances in lignocellulosic biotechnology:A brief review on lignocellulosic biomass and cellulases, *Advances in Bioscience and Biotechnology,* 2014, **5**:246 [Crossref], [Google Scholar], [Publisher]

[46] Zhang J., Rentizelas A., Zhang X., Li J., Sustainable production of lignocellulosic bioethanol towards zero waste biorefinery, *Sustainable Energy Technologies and Assessments*, 2022, **53**:102627 [Crossref], [Google Scholar], [Publisher]

[47] Ojeda K., Sánchez E., Kafarov V., Sustainable ethanol production from lignocellulosic biomass–Application of exergy analysis, *Energy*, 2011, **36**:2119 [Crossref], [Google Scholar], [Publisher]

[48] Maryana R., Ma'rifatun D., Wheni A.I., Satriyo K.W., Rizal W.A., Alkaline pretreatment on sugarcane bagasse for bioethanol production, *Energy Procedia*, 2014, **47**:250 [Crossref], [Google Scholar], [Publisher]

[49] Ramadoss G., Muthukumar K., Influence of dual salt on the pretreatment of sugarcane bagasse with hydrogen peroxide for bioethanol production, *Chemical Engineering Journal*, 2015, **260**:178 [Crossref], [Google Scholar], [Publisher]

[50] Nawaz A., Huang R., Junaid F., Feng Y., Haq I.U., Mukhtar H., Jiang K., Sustainable production of bioethanol using levulinic acid pretreated sawdust. *Frontiers in Bioengineering and Biotechnology*, 2022, **10**:937838. [Crossref], [Google Scholar], [Publisher]

[51] Mizik T., Economic aspects and sustainability of ethanol production—a systematic literature review, *Energies*, 2021, **14**:6137 [Crossref], [Google Scholar], [Publisher]

[52] Broda M., Yelle D.J., Serwańska K., Bioethanol production from lignocellulosic biomass—challenges and solutions, *Molecules*, 2022, **27**:8717 [Crossref], [Google Scholar], [Publisher]

[53] Adewuyi A., Underutilized lignocellulosic waste as sources of feedstock for biofuel production in developing countries, *Frontiers in Energy Research*, 2022, **10**:741570. [Crossref], [Google Scholar], [Publisher]

[54] Devi A., Bajar S., Kour H., Kothari R., Pant D., Singh A., Lignocellulosic biomass valorization for bioethanol production:a circular bioeconomy approach, *Bioenergy Research*, 2022, **15**:1820 [Crossref], [Google Scholar], [Publisher]

[55] Mizik T., Economic aspects and sustainability of ethanol production—a systematic literature review, *Energies*, 2021, **14**:6137 [Crossref], [Google Scholar], [Publisher]

[56] Saini J.K., Saini R., Tewari L., Lignocellulosic agriculture wastes as biomass feedstocks for second-generation bioethanol production:concepts and recent developments. 2015, **3**:337 [Crossref], [Google Scholar], [Publisher]

Copyright © 2024 by SPC (Sami Publishing Company) + is an open access article distributed under the Creative Commons Attribution License (CC BY) license (https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Archive of SID.ir